



## DATA SHEET

# CISCO VPN CLIENT

## Supports Easy VPN Remote

### INTRODUCTION

The Cisco® VPN Client is software that enables customers to establish secure, end-to-end encrypted tunnels to any Cisco Easy VPN server. This thin-design, IP Security (IPSec)-compliant implementation is available from Cisco.com for customers with Cisco SMARTnet® support, and is included free of charge with Cisco VPN 3000 Series concentrators, Cisco ASA 5500 Series security appliances, and most Cisco PIX security appliances. The client can be preconfigured for mass deployments and initial logins require very little user intervention. VPN access policies and configurations are downloaded from the central gateway and pushed to the client when a connection is established, allowing simple deployment and management.

The Cisco VPN Client supports Windows 98, ME, NT 4.0, 2000, and XP; Linux (Intel); Solaris (UltraSparc 32- and 64-bit); and Mac OS X 10.2, 10.3, and 10.4.

The Cisco VPN Client is compatible with the following Cisco products (Cisco Easy VPN servers):

- Cisco VPN 3000 Concentrator Software Version 3.0 and later
- Cisco IOS® Software Release 12.2(8)T and later
- Cisco PIX® Security Appliance Software Version 6.0 and later
- Cisco ASA 5500 Series Software Version 7.0 and later

### FEATURES AND BENEFITS

- Support for Windows 98, ME, NT 4.0, 2000, and XP; Linux (Intel); Solaris (UltraSparc 32- and 64-bit); and Mac OS X 10.2, 10.3, and 10.4.
- Automatic software updates (Windows 2000 & XP) makes deploying new client versions hassle free-new in v4.6
- VPN Virtual Interface Adapter present on Windows 2000 and XP
- Application Programming Interface (API) allows you to control operation of the VPN client from another application-new in v4.6
- System coexistence with Microsoft L2TP/IPsec client
- MSI (Windows Installer) package available for NT, 2000, and XP
- Intelligent peer availability detection (DPD)
- Simple Certificate Enrollment Protocol (SCEP)
- Data compression (LZS)
- Command-line options for connecting, disconnecting, and connection status
- Configuration file with option locking
- Support for Microsoft network login (all platforms)
- Domain Name System (DNS) including DDNS/DHCP computer name population, Split DNS,
- Windows Internet Name Service (WINS), and IP address assignment
- Load balancing and backup server support
- Centrally controlled policies (including backup server list)
- Integrated personal firewall (stateful firewall): Zone Labs technology-Windows only
- Personal firewall enforcement: Cisco Security Agent, Sygate, Zone Alarm-Windows only

- Integration with the iPass remote access client software, including: one-click (single sign-on), VPN auto-teardown, and Windows pre-login support-Windows only.
- Client connection auto initiation for wireless LAN environments

## CISCO EASY VPN

Cisco Easy VPN, a software enhancement for existing Cisco routers and security appliances, greatly simplifies VPN deployment for remote offices and teleworkers. Based on the Cisco Unified Client Framework, Cisco Easy VPN centralizes VPN management across all Cisco VPN devices thus reducing the complexity of VPN deployments. Cisco Easy VPN enables an integration of VPN remotes-Cisco routers, Cisco PIX Security Appliances, Cisco VPN concentrators or software clients-within a single deployment with a consistent policy and key management method thus simplifying remote side administration.

**Table 1.** Product Specifications

Description	Specification
<b>Operating Systems</b>	Support for Windows 98, ME, NT 4.0, 2000, and XP; Linux (Intel); Solaris (UltraSparc 32- and 64-bit); and Mac OS X 10.2, 10.3, and 10.4.
<b>Tunneling Protocols</b>	IPSec Encapsulating Security Payload (ESP), PPTP, L2TP, L2TP/IPSec, Network Address Translation (NAT) Transparent IPSec, Ratified IPSec/UDP (with autodetection and fragmentation avoidance), IPSec/TCP
<b>Encryption/Authentication</b>	IPsec (ESP) using Data Encryption Standard (DES)/Triple DES (3DES) (56/168-bit) or AES (128/256-bit) with MD5 or SHA
<b>Key Management</b>	Internet Key Exchange (IKE)-Aggressive and Main Mode (Digital certificates) Diffie-Hellman (DH) Groups 1, 2, and 5 Perfect Forward Secrecy (PFS) Rekeying
<b>Data Compression</b>	Lempel-Ziv standard (LZS) compression
<b>Digital Certificates</b>	<ul style="list-style-type: none"> <li>• The supported enrollment mechanisms are Simple Certificate Enrollment Protocol (SCEP) and Certificates enrolled with Microsoft Internet Explorer.</li> <li>• Supported certificate authorities (CAs) include: Entrust, Netscape, Baltimore, RSA Keon, Verisign, and Microsoft.</li> <li>• Entrust ESP and Entelligence Client support</li> <li>• Smartcards: Supported via MS CAPI (CRYPT_NOHASHOID) include: Activcard (Schlumberger cards), Aladdin, Gemplus and Datakey.</li> </ul>
<b>Authentication</b>	<ul style="list-style-type: none"> <li>• Extended Authentication (XAUTH)</li> <li>• Remote Authentication Dial-In User Service (RADIUS) with support for: <ul style="list-style-type: none"> <li>State/Reply-Message attributes (token cards)</li> <li>Kerberos/Active Directory authentication</li> <li>Security Dynamics (RSA SecurID Ready)</li> <li>Microsoft NT Domain authentication</li> <li>MSCHAPv2-NT Password Expiration</li> <li>X.509v3 digital certificates</li> </ul> </li> <li>• External user authorization information may be obtained via LDAP or RADIUS</li> </ul>
<b>Certifications</b>	FIPS 140-2 Level 1 (v3.6)
<b>Profile Management</b>	Client can be easily distributed with preconfigured Profile Configuration Files (PCFs)
<b>Policy Management</b>	ISAKMP Configuration Method (Mode-Config) centrally controlled policies including DNS/Split DNS, WINS, IP Address, and Default Domain Name. Ability to save connection password, split tunneling/local LAN access control/networks, remote access load balancing, Centralized Protection Policy (firewall), personal firewall requirement (Are You There?), automatic software updates

**Table 2.** Remote Access Feature Comparison Chart

	Cisco VPN 3000	Cisco ASA 5500	Cisco PIX Security Appliance	Cisco IOS
Version used for Feature Chart	4.7	7.0	7.0	12.3(8)T or 12.2(18)SX
All Cisco Easy VPN Client OS Support	Y	Y	Y	Y
Apani (Mac OS 8/9) VPN Client Compatibility Tested	Y	N	N	N
<b>Basic Client Functionality</b>				
DES/3DES, MD5/SHA	Y	Y	Y	Y
AES (128, 256 bit)	Y	Y	Y	Y
PreShared Secret (Group)	Y	Y	Y	Y
DNS, WINS, Default Domain, IP	Y	Y	Y	Y
Split DNS Support	Y	Y	Y	Y
Dynamic DNS/DHCP (Computer name population)	Y	Y	Y	N
Connection Auto-Initiation	Y	Y	Y	Y
<b>Authentication</b>				
RADIUS	Y	Y	Y	Y
RADIUS with State+Reply Tokens	Y	Y	Y	Y
RADIUS with NT Password Expire	Y	Y	Y	Y
Native RSA SecurID (SDI)	Y	Y	Y	N
Native Kerberos/Active Directory	Y	Y	Y	N
Native NT Domain	Y	Y	Y	N
Certificate/Entelligence/Smartcard	Y	Y	Y	Y
Peer Detection (DPD)	Y	Y	Y	Y
Backup Server List (Client)	Y	Y	Y	Y
Backup Server List (Central Control)	Y	Y	Y	Y
Rekeying	Y	Y	Y	Y
Idle Timeout Support	Y	Y	Y	Y
Max Connection Limit	Y	Y	Y	Y
User IP Filters	Y (including Dynamic ACLs)	Y (including Dynamic ACLs)	Y (including Dynamic ACLs)	Y through ACLs
RADIUS Group Lock	Y	Y	Y	Y
<b>Address Assignment</b>				
Internal Address Pool	Y	Y	Y	Y
DHCP	Y	Y	Y	N
RADIUS	Y	Y	Y	Y
<b>Advanced Functionality</b>				
Data Compression	Y	Y	Y	Y
Concentrator Banner Message	Y	Y	Y	N
Automatic Software Updates	Y—Centrally Controlled	Y—Centrally Controlled	Y	Y
Software Update Notification	Y	Y	Y	N
Saved Password Control	Y	Y	Y	Y

	Cisco VPN 3000	Cisco ASA 5500	Cisco PIX Security Appliance	Cisco IOS
Tunnel Default Gateway	Y	Y	Y	Y
Clustering/Load Balancing	Y	Y	N	N
IPSec to MPLS, 802.1q or PVC Mapping	N	N	N	Y
<b>Tunneling Methods</b>				
All Tunneling/Split Tunneling	Y	Y	Y	Y
Local LAN Access Permission	Y	Y	Y	Y
Ratified IPSec/UDP NAT Transparency (including auto-detection and fragmentation avoidance)	Y	Y	Y	Y
Legacy NAT/PAT Transparency (UDP)	Y	Y	Y	N
TCP-Based IPsec (TCP)	Y	Y	Y	N
<b>Client Personal Firewall Support</b>				
User Controlled (Always On)	Y	Y	Y	Y
Cisco Security Agent/Sygate/Zone Alarm Enforcement (AYT)	Y	Y	Y	N
Centralized Protection Policy (CPP)	Y	Y	Y	N
Zone Labs Integrity	Y	N	N	N

## ORDERING INFORMATION

### Where to Buy Cisco Products

Visit [http://www.cisco.com/public/ordering\\_info.shtml](http://www.cisco.com/public/ordering_info.shtml).

### Product and Part Numbers

Available for customers with SMARTnet™ support at <http://www.cisco.com/kobayashi/sw-center/vpn/client/>.

**Table 3.** Part Numbers for the Cisco VPN Client

Description	Part Number
Cisco VPN Client	CVPN-CLIENT-K9=

### Documentation

For part numbers for product specific documentation, visit <http://www.cisco.com/public/support/tac/tools.shtml#geninfo>.

**Corporate Headquarters**

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 526-4100

**European Headquarters**

Cisco Systems International BV  
Haarlerbergpark  
Haarlerbergweg 13-19  
1101 CH Amsterdam  
The Netherlands  
www-europe.cisco.com  
Tel: 31 0 20 357 1000  
Fax: 31 0 20 357 1100

**Americas Headquarters**

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-7660  
Fax: 408 527-0883

**Asia Pacific Headquarters**

Cisco Systems, Inc.  
168 Robinson Road  
#28-01 Capital Tower  
Singapore 068912  
www.cisco.com  
Tel: +65 6317 7777  
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus  
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel  
Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal  
Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan  
Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2005 Cisco Systems, Inc. All rights reserved. CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, Packet, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, StrataView Plus, TeleRouter, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0502R) 205298.D\_ETMG\_KM\_6.05

